

W12N8-350

12" - 350 W - 98 dB - 8 Ohm



NOMINAL SPECIFICATIONS

Nominal Diameter	300 mm (12 in)
Overall Diameter	315.2 mm (12.4 in)
Bolt Circle Diameter	298.5 mm (11.75 in)
Baffle Cutout Diameter	283.5 mm (11.16 in)
Depth	140.6 mm (5.54 in)
Flange and Gasket Thickness	12.1 mm (0.48 in)
Net Weight	2.9 kg (6.38 lb)
Shipping Box (Single Carton Box)	350 x 350 x 200 mm (13.8 x 13.8 x 7.9 in)
Shipping Weight	3.7 kg (8.14 lb)

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
 (2) Maximum power is defined as 3dB greater than nominal power.
 (3) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
 (4) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	6 Ohm
AES Power Handling (1)	350 W
Maximum Power Handling (2)	700 W
Sensitivity (1W/1m)	98 dB
Frequency Range	50÷4000 Hz
Voice Coil Diameter	77 mm (3 in)
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	15 mm (0.59 in)
Magnetic Gap Depth	10.5 mm (0.41 in)
Flux Density	1.15 T

THIELE & SMALL PARAMETERS

Fs	50 Hz
Re	5.1 Ohm
Qes	0.32
Qms	6.91
Qts	0.30
Vas	65 dm ³ (2.29 ft ³)
Sd	486.5 cm ² (75.4 in ²)
Xmax (3)	5.75 mm
Xdamage (4)	15 mm
Mms	52.3 g
Bl	16.1 N/A
Le	0.78 mH
Mmd	46.3 g
Cms	0.21 mm/N
Rms	2.3 kg/s
Eta Zero	2.45 %

